

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/531604



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036527 A1

(51) International Patent Classification⁷: G08C 17/02,
23/04, 19/28

[NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:
PCT/IB2003/004222

(74) Agent: COHEN, Julius, S.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(22) International Filing Date:
19 September 2003 (19.09.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079334.5 18 October 2002 (18.10.2002) EP


(71) Applicant (*for all designated States except US*): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and
(75) Inventor/Applicant (*for US only*): ZWART, Paul

[Continued on next page]

(54) Title: MEDICAL EXAMINATION SYSTEM



(57) Abstract: The invention refers to a medical examination system (1) comprising a medical examination device (2) and a control device (3) to operate the medical examination device. The control device transmits signals comprising control signals accompanied by an identification code (Key A). The examination device is provided with means (10) to verify the identification code and is arranged to accept the corresponding control signals when the identification code is correct and to reject the corresponding control signals when the identification code is not correct. The examination system further comprises means (6) for automatically communicating the identification code between the control device (3) and the examination device (2).

WO 2004/036527 A1

**Declaration under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,*

DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Medical examination system

The present invention relates to a medical examination system comprising a medical examination device and a control device to operate the medical examination device, wherein the control device transmits signals comprising control signals accompanied by an identification code and wherein the examination device is provided with means to verify the
5 identification code and is arranged to accept the corresponding control signals when the identification code is correct and to reject the corresponding control signals when the identification code is not correct.

Such a medical examination system is known from the international patent application WO 00/30416. In the known system the medical examination device it is intended
10 to operate has to be made known to the control device first. This needs to be performed by a manual coupling action, for instance by placing the control device in front of the medical examination device or by establishing a cable connection between said devices. During this coupling the identification code necessary for wireless operation is transmitted.

The manual character of the necessary coupling act introduces a potential
15 danger, since it can easily be forgotten. When a wireless control device is removed from an examination room it will still operate the medical examination device in that examination room. When the control device is brought into another examination room it will operate the medical examination device in the previous examination room until the necessary coupling to the medical examination device in the same examination room is established. Evidently this
20 may lead to potentially very dangerous situations. Probably the forgotten coupling act will only be discovered while one tries in vain to operate the medical examination device in the same examination room during which one is not knowingly operating the medical examination device in the previous examination room. In another situation when the control device is kept in storage, for repair or recharging, a potentially dangerous situation occurs
25 each time the control device is inadvertently activated.

It is an object of the invention to provide a device of the type as described above that solves this problem.

The medical examination device according to the invention is therefore characterised in that the examination system further comprises means for automatically

communicating the identification code between the control device and the examination device.

5 In a first preferred embodiment of the device according to the invention the communication means are arranged to receive the identification code from the medical examination device for transmittance to the control device.

 According to a further preferred embodiment the communication means are arranged for periodically transmitting the identification code and the control device is
10 provided with memory means for temporal storage of the identification code. Advantageously the control device automatically forgets the identification code when it is out of reach of the communication means.

 Preferably the communication means comprise Infra Red transmitter means and the control device is provided with Infra Red receiver means. Infra Red communication
15 means have a limited reach thus allowing the identification code to be transmitted only in a confined area, such as the examination room in which the examination device is located.

 In a second preferred embodiment of the device according to the invention the communication means are arranged to receive the identification code from the control device for transmittance to the examination device.

20 In a practical embodiment the communication means comprise interrogation means for periodically retrieving the identification code from the control device.

 Preferably the interrogation means comprise an RFID reader and the control device is provided with an RFID tag. RFID means have a limited reach thus allowing the identification code to be transmitted only in a confined area, such as the examination room in
25 which the examination device is located.

 In yet a further preferred embodiment the control device is provided with a radio frequent transmitter and the examination device is provided with a radio frequent receiver. The use of radio frequent (RF) equipment allows the signals to travel undisturbed thus assuring a high degree of reliability of the control over the system.

30 In an elegant embodiment the identification code comprises a room identification code identifying the room in which the examination device is located.

 In a practical embodiment the examination device comprises an X-ray device. As an X-ray device is potentially dangerous for human health and needs to be operated only

under professional supervision the invention is very useful in combination with an X-ray system. In a further practical embodiment the control device is an X-ray foot switch.

The invention also refers to a method for automatically communicating an identification code between a control device and a medical examination device in a medical examination system according to a first embodiment of the invention comprising the steps of: receiving the identification code from the medical examination device by the communication means; transmitting the identification code periodically to the control device by the communication means; and temporally storing the identification code in the memory means of the control device.

The invention also refers to a method for automatically communicating an identification code between a control device and a medical examination device in a medical examination system according to a first embodiment of the invention, comprising the steps of: periodically interrogating the control device by the communication means for retrieving the identification code; and transmitting the identification code to the examination device by the communication means.

The invention will be further explained by means of the attached drawing, in which:

Figure 1 schematically shows a first embodiment of the device according to the invention;

Figure 2 schematically illustrates the functioning of the first embodiment;

Figure 3 shows a block diagram illustrating the steps of a first embodiment of a method according to the invention;

Figure 4 schematically shows a second embodiment of the device according to the invention; and

Figure 5 shows a block diagram illustrating the steps of a second embodiment of a method according to the invention.

In all figures equal objects are denoted with equal reference numerals.

Figure 1 schematically shows a first embodiment of medical examination system according to the invention. Medical examination system 1 comprises a medical examination device, in this preferred embodiment an X-ray device 2, and a wireless control

device 3 for remote operation of the X-ray device 2. In the example shown the wireless control device is an X-ray foot switch 3 provided with battery supply.

The foot switch 3 is provided with a radio frequent (RF) transmitter 4 to transmit signals comprising control signals accompanied by an identification code to the X-ray device 2. The X-ray device 2 is provided with a radio frequent receiver 5 to receive said signals.

The examination system 1 further comprises communication means 6 comprising Infra Red transmitter means for automatically periodically transmitting the identification code to the foot switch 3. The foot switch 3 is provided with Infra Red receiver means 7 for receiving the identification code. In the foot switch memory means 8 are present for temporal storage of the identification code. Eraser means 9 are used to erase the identification code from the memory means after a predefined period of time.

The X-ray device 2 is coupled to the transmitter means 6 to provide the identification code. Any unique code may be used as identification code. Preferably the identification code comprises a room identification code identifying the examination room A in which the X-ray device 2 is located.

The X-ray device 2 is provided with means 10 to verify the identification code and is arranged to accept the corresponding control signals when the identification code is correct and to reject the corresponding control signals when the identification code is not correct.

Figure 2 schematically illustrates the functioning of the first embodiment of the system according to the invention. Two adjacent examination rooms A and B are shown that are separated by a wall W. The medical examination system 1 is situated in room A. In room B another examination system 11 according to the invention is located having similar components as system 1. The corresponding components of system 11 are denoted with corresponding reference numerals incremented by 10. System 11 comprises: an X-ray device 12 having an RF receiver 15 and verification means 20, and communication means 16.

System 11 uses the foot switch 3 from system 1 provided with an RF transmitter 4, Infra Red receiver means 7, memory means 8 and eraser means 9.

Figure 3 shows a block diagram illustrating the functioning of the system according to the invention when the foot switch 3 is removed from room A and brought into room B.

In step 10 X ray system 2 in room A sends a room identification code Key A to the communication means 6.

In step 20 communication means 6 periodically send the room identification code Key A to the foot switch 3 which is present in room A. In this example one or more omni-directional Infrared senders 6 are used. As this provides multi-path connections by reflection from walls and other objects, the Key A signal will not be blocked by intervening objects. As Infra Red radiation does not penetrate the walls the signal will be confined to room A.

In step 30 the foot switch 3 receives the room identification code Key A and temporally stores it in the memory means 8.

In step 40 the foot switch 3 is removed from room A.

10 In step 50 the eraser means 9 erase Key A from the memory means 8. The eraser means may comprise standard data eraser means that automatically operate after a predetermined time period. As the foot switch 3 is located outside room A it can no longer receive Key A.

15 In step 60 foot switch 3 is accidentally activated and transmits RF control signals without a valid identification code.

In step 70 X-ray system 2 and X-ray system 12 may both receive the RF signals, but the verification means 10 respectively 20 will reject the control signals because of the invalid identification code and both the X-ray system 2 and X-ray system 12 will not respond to the control signals. The verification means 10 can for example be arranged to compare the identification code accompanying the signals from foot switch 3 to the room identification key A the X-ray system 2 has sent to the communication means 6 in step 10.

In step 80 foot switch 3 is brought into room B.

25 In step 90 communication means 16 periodically send the room identification code Key B to the foot switch 3. Preferably one or more omni-directional Infrared senders 16 are used to assure that the Key B signal will not be blocked by intervening objects and will be confined to room B.

In step 100 the foot switch 3 receives the room identification code Key B and temporally stores it in the memory means 8.

30 Step 90 is repeated after a predetermined time period. Step 100 will be performed as long as foot switch 3 is located in room B.

In step 110 the foot switch 3 is activated and transmits control signals accompanied by Key B.

In step 120 the RF receiver 15 receives the signals, the verification means 20 verify key B as the correct identification code and of X-ray system 12 acts according to the control signals.

In step 130 RF receiver 5 receives the signals, the verification means 10 verify key B as a false identification code and X-ray system 2 is not activated by the control signals.

Figure 4 schematically shows a second embodiment of the system according to the invention. Medical examination system 21 partly corresponds to system 1. The corresponding components of system 21 are denoted with corresponding reference numerals incremented by 20. System 21 comprises: an X-ray device 22 having an RF receiver 25 and verification means 30, and a foot switch 23 having an RF transmitter 24, Radio Frequency Identification (RFID) tag means 27 and memory means 28, and communication means 26 comprising an RFID reader 26.

In the memory means 28 of the foot switch 23 an identification code Key C is stored. The same identification code Key C is stored in the RFID tag 27. The communication means 26 are arranged as interrogation means for periodically retrieving the identification code from the foot switch 23. The interrogation means comprise an RFID reader 31 and the foot switch 23 is provided with an RFID device 27. The RFID reader sends an RF pulse to which the RFID tag responds by returning an RF signal comprising the unique identification code Key C of the foot switch 23. The area in which the RFID reader is sensitive to the response of the RFID tag is typically a few square meters. The RFID reader 26 sends the RFID response signal comprising the identification code to the X ray device 22. The RFID reader 26 is hereto connected to the X ray device 22 by cable.

The verification means 30 are arranged to verify the accompanying identification code of each incoming control signal for the X ray device 22 with Key C and will thus accept only control signals originating from the control device having Key C as unique identification code that has made its presence known in the same examination room C.

It will be clear to a person skilled in the art that one or more foot switches can be added to the system in both embodiments allowing the system to be operated from various different positions.

Furthermore the medical examination system according to the invention is also suitable in a situation wherein two medical examination systems are situated in the same examination room. In both embodiments each control device will then be arranged to send control signals accompanied by a room identification code as well as a control device

identification code to the corresponding examination device. The control device identification code should be unique in the context of an examination room. Said control device identification code should also be made known to the corresponding examination device. This can be performed by means of techniques known per se in the art. The
5 verification means will be arranged to only accept the control signals when both the room identification code and the control device identification code are verified.

In the second embodiment 21 (see figure 4) due to the limited response area of the RFID reader 26 the room identification code sent by the RFID tag 27 naturally will reach only the RFID reader 26. In the same manner the room identification code sent by the RFID
10 tag of a similar additional system in the same examination room naturally will reach only the RFID reader of the additional system. This will reduce the chance of errors occurring in case the communication of the control device identification code failed.

In the first embodiment 1 of the invention however, in case of failure to communicate the control device identification code, possible errors will now only occur in
15 the same examination room under direct supervision of skilled personnel that has the possibility to intervene to prevent real danger.

Summarizing the invention refers to a medical examination device operable by a remote control device, wherein means are provided for automatic assignment of an identification code to the control device and/or the medical examination device, which code
20 is necessary for operation of the medical examination device by the control device.

The invention is thus of course not limited to the described or shown embodiments, but generally extends to any embodiment, which falls within the scope of the appended claims as seen in light of the foregoing description and drawings.

CLAIMS:

1. Medical examination system comprising a medical examination device and a control device to operate the medical examination device, wherein the control device transmits signals comprising control signals accompanied by an identification code and wherein the examination device is provided with means to verify the identification code and is arranged to accept the corresponding control signals when the identification code is correct and to reject the corresponding control signals when the identification code is not correct, characterized in that, the examination system further comprises communication means for automatically communicating the identification code between the control device and the examination device.
2. Medical examination system according to claim 1, wherein the communication means (6; 16) are arranged to receive the identification code from the medical examination device for transmittance to the control device.
3. Medical examination system according to claim 1 or 2, wherein the communication means are arranged for periodically transmitting the identification code and the control device is provided with memory means for temporal storage of the identification code.
4. Medical examination system according to claim 1, 2 or 3, wherein the communication means comprise Infra Red transmitter means and the control device is provided with Infra Red receiver means.
5. Medical examination system according to claim 1, wherein the communication means are arranged to receive the identification code from the control device for transmittance to the examination device.

6. Medical examination system according to claim 5, wherein the communication means comprise interrogation means for periodically retrieving the identification code from the control device.

7. Medical examination system according to claim 6, wherein the interrogation means comprise an RFID reader and the control device is provided with an RFID tag.

8. Medical examination system according to one or more of the preceding claims, wherein the control device is provided with a radio frequent transmitter and the examination device is provided with a radio frequent receiver.

9. Medical examination system according to one or more of the preceding claims, wherein the identification code comprises a room identification code identifying the room in which the examination device is located.

10. Medical examination system according to one or more of the preceding claims, wherein the examination device comprises an X-ray device.

11. Medical examination system according to claim 10, wherein the control device is an X-ray foot switch.

12. Method for automatically communicating an identification code between a control device and a medical examination device in a medical examination system according to one or more of the preceding claims 1 through 4, and 8 through 11, comprising the steps of:

a) receiving the identification code from the medical examination device by the communication means;

b) transmitting the identification code periodically to the control device by the communication means; and

c) temporally storing the identification code in the memory means of the control device.

13. Method for automatically communicating an identification code between a control device and a medical examination device in a medical examination system according to one or more of the preceding claims 5 through 11, comprising the steps of:

- a) periodically interrogating the control device by the communication means for retrieving the identification code; and
- b) transmitting the identification code to the examination device by the communication means.

1/4




Fig.1

2/4




Fig.2

3/4




Fig.3

4/4




Fig.4

INTERNATIONAL SEARCH REPORT

International Application No.

PC 03/04222

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G08C17/02 G08C23/04 G08C19/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G08C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 94 06106 A (SEIKI OY ; KUPIAINEN JUHANI (FI)) 17 March 1994 (1994-03-17)	1-4, 8-12
Y	page 1, line 23-27 page 2, line 30 - page 3, line 5 page 3, line 22-24 page 10, line 21-24 page 11, line 6-10 page 11, line 16-26	5-7, 13
Y	WO 92 15977 A (SYDEC NV) 17 September 1992 (1992-09-17) page 3, line 15-31	5-7, 13
	--- -/-- ---	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

25 February 2004

Date of mailing of the international search report

05/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Chimet, D

INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 03/04222

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 864 293 A (HEWLETT PACKARD CO) 16 September 1998 (1998-09-16) column 3, line 39-41 column 3, line 55 -column 4, line 16 column 5, line 13-29 -----	1-13

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP93/03/04222

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9406106	A	17-03-1994	FI 923881 A	01-03-1994
			AU 4960793 A	29-03-1994
			WO 9406106 A1	17-03-1994
			GB 2275553 A	31-08-1994
			SE 9401442 A	28-06-1994
WO 9215977	A	17-09-1992	WO 9215977 A1	17-09-1992
EP 0864293	A	16-09-1998	EP 0864293 A1	16-09-1998
			DE 69700384 D1	09-09-1999
			DE 69700384 T2	25-11-1999
			JP 11317985 A	16-11-1999
			US 6150951 A	21-11-2000

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☒ OTHER: holes between words.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.